

WINNEBAGO

HIKE 100 / Specifications



WEIGHTS & MEASURES	1316SB	1316FB	1316TB	1316DB	1316MB
Exterior Length	15'11"	15'11"	15'11"	15'11"	15'11"
Exterior Height ¹	9'11"	9'11"	9'11"	9'11"	9'11"
Exterior Width ²	8'1"*	8'1"*	8'1"*	8'1"*	8'1"*
Interior Height	6'5"	6'5"	6'5"	6'5"	6'5"
GVWR (lbs.)	4,200	4,200	4,200	4,200	4,200
Axles (lbs.)	1 @ 4,000	1 @ 4,000	1 @ 4,000	1 @ 4,000	1 @ 4,000
Dry Weight (lbs.)	3,284	3,178	3,122	3,170	3,156
Dry Hitch Weight (lbs.)	462	546	576	536	566
Hitch Height	28"	28"	28"	28"	28"
Freshwater Tank Capacity ³ (gal.)	31	31	31	31	31
Holding Tank Capacity – Black ³ (gal.)	4.75	4.75	4.75	4.75	4.75
Holding Tank Capacity – Gray ³ (gal.)	25	25	25	25	25
Water Heater Capacity (gal.)	6	6	6	6	6
LP Capacity ⁴ (lbs.)	20	20	20	20	20
Furnace (BTU)	18,000	18,000	18,000	18,000	18,000
Awning Length	10'	10'	10'	10'	10'
Tire Size	225/75R16E	225/75R16E	225/75R16E	225/75R16E	225/75R16E
Sleeps ⁵	4	3	3	3	2

* 7' box, 8'1" with nerf bars

Interior

MOLLE panel (Not applicable on 1316MB)

Flip-down table (Only applicable on 1316SB)

TransCore™ fully composite flooring

JBL® portable Bluetooth® speaker

Interior TV prep

Folding table (Only applicable on 1316TB, 1316SB, and 1316MB)

Designated wardrobe

Galley

1.1 cubic ft. convection microwave

3.3 cubic ft. 12-volt refrigerator

Undermount single bowl stainless steel sink with cover

Portable induction cooktop

Pull-out countertop extension

Contemporary cabinet style

Bath

Wet bath with power vent

Integrated gear drying racks

Cassette toilet

Cubby for dry storage

Bedroom

Versatile sleeping arrangements

Sleeps up to 4 adults depending on the floorplan

Exterior

NXG engineered frame

2" thick FILON® MAX fiberglass sidewalls with Azdel Onboard® composite panels

Fully walkable roof

Side-mount ladder

Weather proof junction box

Premium Suspension Upgrade: BAL® Independent Suspension with Dexter® TorFlex® torsion stub axles

Goodyear® Wrangler® 16" off-road tires

Aluminum wheel assemblies

Goodyear Wrangler 16" spare tire

Powered patio awning with LED lighting

Rear dual door opening 60" x 60" with screens (Only applicable on 1316SB)

Manual rear and off-camp side batwing awning with drop-down panels for exterior shower

Designated outdoor shower

Power tongue jack

Power stabilization jacks

All LED exterior lighting with reverse lights integrated into brake lights

Fully enclosed underbelly with radiant foil insulation

Powder coated roof exoskeleton

Powder coated fender gear boxes

2" accessory receiver hitch with 350 lbs. capacity

Lower nerf bars integrated into the frame

Exterior patio side LP quick connect

Thick core slam latch baggage doors

Outdoor kitchen (Only applicable on 1316FB and 1316DB)

Portable Truma® cooler (Only applicable on 1316FB and 1316DB)

Protective metal front and side brush guard

Quick connect spray port

Camp side TV prep

Furrion side-mount camera prep

Furrion back-up camera prep

Heating & Cooling System

6-gallon gas/electric/DSI water heater

18,000 BTU LP furnace

13,500 low-profile roof A/C

CSA vents

20lb. LP tank

Electrical System

200-watt solar panel with 30-amp charge controller and resettable breaker

Side-mount solar prep for additional panel

Inverter prep

Winnebago all-in-one control panel

12-volt tank pad heaters with interior switch

USB/ USB-C charge ports

Wi-Fi Prep integrated into King® Omni Antenna

Wireless cellphone charger

Tire Pressure Monitoring System prep

Plumbing System

6-gallon gas/electric/ DSI water heater

31-gallon freshwater tank

4.75-gallon cassette toilet

25-gallon gray tank

Warranty

See your dealer for complete warranty information.

FOOTNOTES

- The height of each model is measured to the top of the tallest standard feature and is based on the curb weight of a typically equipped unit. The actual height of our vehicle may vary by several inches depending on chassis or equipment variations. Please contact your dealer for further information.
- Floorplans feature a wide-body design - over 96-inches. In making your purchase decision, you should be aware that some states restrict access on some or all state roads to 96-inches in body width. Before making your purchase decision, you should confirm the road usage laws in the states of interest to you.
- Capacities are based on measurements prior to tank installation. Slight capacity variations can result due to installation applications.
- Capacities shown are tank manufacturer's listed water capacity (W.C.). Actual filled LP capacity is 80% of listing due to overfilling prevention device on tank.
- Sleeping capacity is the maximum based on a specific floorplan.

Because features, specification, equipment, and options may vary from those highlighted here, the buyer is responsible for confirming with the dealer the features, specifications, equipment, and options included in their specific vehicle.

In addition, Winnebago's program of continuous product improvement may result in changes to vehicle specifications, equipment, model availability, and price without notice.